永嘉跃龙密封件有限公司 Yongjia Yuelong Sealing Parts Co., Ltd 产品质量证明书 Product quality certificate

客户Customer: ONERO VALVE GROUP CO; LTD

执行标准Executive standard: GB/T23658 -2009

NO: 0002023022301

产品名称 Product name	O型圈 O-	RING	规格型号 Specificatio		efer to achment	材质Material	VITON AED
数 量 QTY	Refer to att	achment	批 号 Lot number	202	3022301	出厂日期 Delivery Date	2023-2-23
标准要求Requirement		O型圈 O-RING(VITO			ON AED)		结论 Conclusion
出厂项目Items		标准要求 Standard requirement			实测值 Measured value		
外观 Appearance		密封圈应没有可影响其功能的缺陷 或不规整。疵点验收执行 GB/T17604The sealing ring should be free of defects or irregularity that can affect its function. Perform GB/T17604 for defects acceptance			合格 Qualified		合格 Qualified
硬度 Hardness		90±5		90		合格 Qualified	
拉伸强度 Tensile strength(MPa)		≥10		23		合格 Qualified	
拉断伸长率EL(%)		≥200		210		合格 Qualified	
压缩永久变形Compression permanent deformation (70°C 24h)		≤18		16		合格 Qualified	
截径公差 Cross section tolerance(GB/T3672.1)		≤6.3±0.5 (6.3~10)±0.7					合格 Qualified
内径公差 Inside diameter tolerance		(10~16)±0.08 (16~25)±1					合格 Qualified
		(25~40)±1.3 (40~63)±1.6					合格 Qualified
	ameter tolerance 3/T3672.1)		~100)±2 ~160)±2.5				合格 Qualified
		(>160)±3 能符合标准GB/T23658-2009标准规定					合格 Qualified

经检验该批次的橡胶O形圈其物理性能符合标准GB/T23658-2009标准规定的要求,尺寸符合图样规定,准予出厂。 After inspection, the physical properties of the batch of rubber O-rings meet the requirements specified in the standard GB/T23658-2009 standard, the size meets the requirements of the drawing, and is allowed to leave the factory.

永嘉跃龙密封件有限公司(公章) Yongjia Yuelong Sealing Parts Co., Ltd

Inspector/time:朱臣康

Approval/Time: 徐丽娟



附页Attache	d sheet
型号SIZE	数量QTY
外 (Outside diameter) 200*8.6	16
外 (Outside diameter) 771*8.6	16
外 (Outside diameter) 528*7	32
外 (Outside diameter) 498*7	32
外 (Outside diameter) 486*4	16
外 (Outside diameter) 245*8.6	24
外 (Outside diameter) 174*8.6	24
	大、竹、茶、村
	HINS - T
	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
	10
	111年十二 5
	「日本
	14